



ecoClean™

eC16 Application Procedures

100% Bio-Based Cleaners

Dilution Rates (in brackets) are general recommendations. Adjust as needed. Although environmentally harmless, use standard precautions when mixing.

Applications for eC16 Concentrate		
Product	Applications	Procedure
Glass Cleaning (1-2 oz/gal) (5 – 10 ml /liter)	Windows, mirrors, eyeglasses, windshields, white boards, museum cases, glass art objects, jewelry, Plexiglas, aquariums, appliances, and counter tops, table tops, floors, wood furniture, stainless steel appliances.	Spray sparingly from 18-24 inches from the surface. Wipe with a clean cloth, then buff and polish with the dry side of cloth. Note: Glass surfaces stay clean up to six times longer than with other glass cleaners, saving you time and labor. An invisible anti-static residue reduces future dust and dirt buildup. Finger prints and smudges can usually be buffed away without re-cleaning.
General Cleaning (2-4 oz/gal) (15 – 30 ml /liter)	General janitorial, countertops, walls, floors, hand cleaner, general cleaning	Spray product lightly over area to be cleaned and wipe with a clean cloth. Alternatively, apply cleaning solution to damp cloth and run over area.
Deck Cleaning (3-4 oz/gal) (15– 20 ml /liter) (5-8 oz/gal) (40– 60 ml /liter)	Vehicle maintenance, work areas, oily or badly soiled floors & carpets, manufacturing, food processing areas, heavy stained walls & doors, granite, marble, natural stone.	Spray product lightly over area to be cleaned and wipe with a clean cloth. If necessary, let product dwell on surface for a few minutes before rinsing.
Medium Cleaning (5-8 oz/gal) (40– 60 ml /liter)	HVAC/R coil cleaning, diesel & gas engines, blood, auto parts, oil & grease, dried on food, concrete & brick, grass or plant stains.	Spray product lightly over area to be cleaned and wipe with a clean cloth. If necessary, let product dwell on surface for 5 - 15 minutes before rinsing.
Heavy Cleaning – (9-12 oz/gal) (45 – 60 ml /liter)	Oil spills, motor and parts cleaning	Spray product liberally over area to be cleaned and let dwell on surface for 5 - 15 minutes before thoroughly rinsing.
Carpet Cleaning (5-8 oz/gal) (40– 60 ml /liter)	For use on synthetic and natural fibers. It leaves no soil attracting residue, so carpets stay cleaner, longer.	Truck Mount Units - Dilute 0.2 to 0.4 ounces per 1 gallon of water. (1.5 – 3 ml /liter) Orbital/Bonnet Cleaning – Dilute 0.2 ounce (1.5ml) per gallon (liter) of water. For light & medium cleaning, spray solution, then bonnet or pad clean. For heavy soil: spray generously, allow time to dwell, bonnet or pad clean with very wet pad, then go over again with a slightly moist bonnet or pad. Agitation with groomer will enhance cleaning results.

For more information about ecoSolv products please visit our website at www.ecosolv.com